

Performance you can trust

## Chainguard Hi-Load Spray

**High performance EP chain and conveyor lubricant with MoS<sub>2</sub>.**

**Designed to effectively displace water, penetrate, lubricate and protect against corrosion, particularly in wet and aggressive conditions.**

### Features

- Temperature range –30°C to 180°C
- Outstanding EP performance (250kg weld load)
- Excellent penetration
- Tenacious water repellent film
- Excellent corrosion protection
- Applied film has good adhesion, reducing dripping or throw off

### Directions for Use

- Shake well
- Hold can upright and spray from a distance of approximately 25cm (10 inches) covering the chain thoroughly

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

## Chainguard Hi-Load Spray

<b>Appearance</b>	Grey liquid
<b>Base type</b>	Mineral oil
<b>Solvent</b>	Hydrocarbon
<b>Propellant</b>	CO <sub>2</sub> (Carbon dioxide)
<b>Temperature range</b>	-30°C to 180°C
<b>Base fluid viscosity at 40°C</b>	18cSt
<b>Base fluid viscosity at 100°C</b>	5cSt
<b>Shell 4 ball (IP 239)(ASTM D2596)</b>	
<b>Weld load</b>	250 kg
<b>Corrosion test (ASTM B 368)</b>	
<b>5% Salt Spray 200 hrs at 35°C</b>	0% (no corrosion)
<b>Storage</b>	Storage area should be: out of direct sunlight. Storage temperature should be kept below 50°C.
<b>Pack sizes – Part Codes</b>	300 ml – p/c 22141

T +44 (0) 113 232 2600  
 F +44 (0) 113 232 2740  
 E customer-service@rocol.com  
 www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
 Certificate No. FM 12448



BS EN ISO 14001  
 Certificate No. EMS 67596



OHSAS 18001  
 Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.  
 There are many factors outside our control or knowledge which affect the use and performance  
 of our products, for which reason it is given without responsibility.