

Performance you can trust

## FOODLUBE® Dismantling Spray



Food grade penetrating spray for effective release

### Product Overview

FOODLUBE® Dismantling Spray is a non-toxic, fast acting, penetrating lubricant which also provides short term corrosion protection for corroded threaded fasteners and other seized components.

FOODLUBE® Dismantling Spray is NSF H1 registered for incidental contact with food making it ideal for use in food, pharmaceutical and other clean industries where a non-toxic product is required or preferred.

### Features and Benefits

- Wide operating temperature range from -20°C to +110°C.
- FOODLUBE® Dismantling Spray provides excellent penetration of rust, scale, grease and general dirt and grime.
- Its fast acting formula provides quick effective release of seized and corroded threaded fasteners.
- FOODLUBE® Dismantling Spray leaves a protective film which provides short term corrosion protection.
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FDA Group 21 CFR 178.3570
- NSF H1 registered - 121617

### Directions for Storage and Use

- Shake aerosol well before use.
- Test compatibility with plastics and rubbers and painted or coated surfaces prior to application.
- Hold can upright and apply from a distance of 15 – 30 cm, coating the components thoroughly and paying particular attention to the seized contact areas.
- In severe cases, applying the product for a second time after several minutes may be beneficial.
- Use only in well ventilated areas and do not apply to very hot surfaces.
- Store below +50°C, out of direct sunlight.
- Shelf life is 5 years from date of manufacture.
- Consult safety data sheet before use.

### Typical Applications

- FOODLUBE® Dismantling Spray is ideal for corroded threaded fasteners and other seized components.
- Specifically designed for use in Food, Pharmaceutical and other clean industries, however, it is also ideal for general industrial applications particularly where a clean product is required.

### Pack Sizes

Pack Size	Part Code
300 ml	15720

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E customer-service@rocol.com  
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of  Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

## FOODLUBE® Dismantling Spray



Food grade penetrating spray for effective release

### Typical Properties

Property	Test Method	Result
Appearance – applied film		Thin colourless film
Base Type		Blend of esters
Solvent		None
Propellant		CO <sub>2</sub> (carbon dioxide)
Odour		Characteristic
Temperature range		-20°C to +110°C
Density (kg/m <sup>3</sup> )		<1
Flash Point (°C)	ASTM D93	>140°C
Water Solubility		Not miscible

Values quoted above are typical and do not constitute a specification.

### Safety Data Sheets

Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL® contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue 06-10

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE