

Performance you can trust

## FOODLUBE® Multi-Paste



**Food grade, non-toxic, multipurpose anti-seize and lubricating paste.**  
**Ideal for, use as an anti-seize/assembly paste, lubricating threads, bushes, slides and small open gears operating in food/clean environments.**

### Features

- Available in Paste or Aerosol form
- Temperature range –30°C to 450°C min.
- Extremely low sulphur & chlorine levels
- Ideal for stainless steel fasteners, particularly at elevated temperatures.
- Economical in use – only requires a thin film for maximum performance.
- Extremely tenacious – resists water wash off
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FDA Group 21 CFR 178.3570
- NSF H1 registered – (Multi Paste - 121614)  
(Multi Paste Spray - 121613)
- DIN V 10517

### Directions for Use

- Apply a thin film, ideally to both surfaces, either manually or by aerosol.
- It is essential that the surfaces are clean and dry prior to application.

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

## FOODLUBE® Multi-Paste

|                                     |  |
|-------------------------------------|--|
| <b>Appearance</b>                   | Smooth, white paste  |
| <b>Carrier</b>                      | Synthetic lubricant  |
| <b>Solids</b>                       | White, non-toxic solids  |
| <b>Multi Paste Spray Propellant</b> | Hydrocarbon  |
| <b>Multi Paste Spray Solvent</b>    | Hydrocarbon  |
| <b>Temperature range</b>            | -30°C to 450°C min.  |
| <b>Coefficient of Friction</b>      | 0.09   |
| <b>Foodlube Multi Paste</b>         | Storage temperature should be controlled to between 1 and 40°C                                   |
| <b>Foodlube Multi Paste Spray</b>   | . Storage temperature should be kept below 50°C. Storage area should be: out of direct sunlight. |
| <b>Pack sizes – Part Codes</b>      |  |
| <b>Foodlube Multi Paste</b>         | 85g – p/c 15750<br>400g – p/c 15851<br>500g – p/c 15753<br>5kg – p/c 15756                       |
| <b>Foodlube Multi Paste Spray</b>   | 400ml – p/c 15751  |

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E customer-service@rocol.com  
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.