



TECHNICAL DATA

SPATTER RELEASE SPRAY

TECHNICAL DATA

Description

ROCOL Spatter Release Spray has been formulated to allow easy removal of weld spatter from metal surfaces, nozzles, jigs and fixtures.

Outstanding Features

- Heat resistant barrier film that prevents the adhesion of weld spatter
- Non silicone – does not affect subsequent galvanising or paint operations
- Will not interfere with weld formation
- Non corrosive

Directions for use

Hold as near upright as possible whilst spraying. Apply a thin even film from a distance of 20-25cm (8-10 inches) to the area near where the weld is to be made. Spatter can be easily removed from the work surfaces by wiping with a cloth, or from the welding nozzle by tapping it on the side of the bench.

Technical Data (typical values)

<i>Appearance:</i>	<i>Aerosol dispensing clear brown liquid</i>
<i>Odour :</i>	<i>Characteristic</i>
<i>Propellant:</i>	<i>Carbon dioxide</i>
<i>Flammability:</i>	<i>Non flammable</i>
<i>Solvents present:</i>	<i>Chlorinated</i>
<i>Storage :</i>	<i>Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.</i>

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

Spatter Release Spray

Pack sizes and part codes

300ml part code 66080

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Spatter Release Spray TDS 6608
Date: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control and knowledge which effect the use and performance of our products
for which reason the information in this publication is given without responsibility

TECHNICAL DATA